




Key
LL 長腳
LP 長針頭
SP 短針頭
RECT 矩形的

釘 扣 說 明 表



釘扣 SERIES	釘 扣 尺 寸	厚 度		最小齒輪 直 徑		釘扣鐵絲 直 徑		每條的 扣數鈎		推 荐 連 結 蕊		釘 扣 機	
		Inches	mm	Inches	mm	Inches	mm	Stand ard	LW #95	size	Diameter (Inches)	手工	電動
#25 SERIES"	#25 SP	UP TO 1/32"	UP TO-0.8	15/16"	24	.025	0.6	85	85	#25	.054-.065	#12 Lancer	Electric
	#25	1/32"-1/16"	0.8-1.6	15/16"	24	.025	0.6	85	85	#25	.054-.065	W/#25	Hydraulic
	#25 LP	1/16"-1/8"	1.6-3.2	15/16"	24	.025	0.6	85	85	#25	.054-.065	Hook	12" .25" .38"
	#25 LL	1/32"-1/16"	0.8-1.6	2"	51	.025	0.6	**85	85	#25	.054-.065	Retainer.	Hook
	#25 LL SP	UP TO 1/32"	UP TO 0.8	2"	51	.025	0.6	**85	85	#25	.054-.065	#25 XLW	Retainer
	#25 LL LP	1/16"-1/8"	1.6-3.2	2"	51	.025	0.6	**85	85	#25	.054-.065		
	#25 LL RECT	1/16"-3/32"	1.8-2.4	2"	51	.024×.026	0.61×0.66	**85	85	#25	.054-.065		
#1 SERIES	#1-D	1/16"-3/32"	1.6-2.4	2"	51	.040	1.0	**50	44	#25	.054-.065	Roller Lancer®	Electric
	#1 A	1/8"-5/32"	2.4-3.2	2"	51	.040	1.0	**50	44	#25	.054-.065	#12 Lancer.	Hydraulic
	#1	3/32"-1/8"	3.2-4.0	2"	51	.040	1.0	**50	44	#25	.054-.065	Microlacer™	12" .25" .38"
	#1-D LL	1/16"-3/32"	1.6-2.4	3"	76	.040	1.0	**50	44	#25	.054-.065	W/#1	W/#1
	#1-A LL	3/32"-1/8"	2.4-3.2	3"	76	.040	1.0	**50	44	#25	.054-.065	Hook	Hook
	#1 LL	1/8"-5/32"	3.2-4.0	3"	76	.040	1.0	**50	44	#25	.054-.065	Retainer	Retainer
REGULAR SERIES	#2 SP	1/8"-5/32"	3.2-4.0	3"	76	.054	1.4	84	38	#13	.093	Roller Lacer®.	Electric
	#2	5/32"-3/16"	4.0-4.8	3"	76	.054	1.4	84	38	#13	.093	Microlacer™.	Hydraulic
	#3-1	1/8"-5/32"	3.2-4.0	3 1/2"	89	.054	1.4	84	38	#13	.093	#12 Lacer.With 12" .25" .38"	
	#3	3/16"-7/32"	4.8-5.6	3 1/2"	89	.054	1.4	84	38	#13	.093	Chain Drive	
	#3 RECT	3/16"-7/32"	4.8-5.6	3 1/2"	89	.052×.057	1.3×1.5	84	38	#13	.093	Attachment	
	#3 4 1/2	7/32"-1/4"	5.6-6.4	3 1/2"	89	.054	1.4	84	38	#13	.093		
	#4	7/32"-1/4"	5.6-6.4	4"	102	.054	1.4	84	38	#12	.109		
	\$4-2	5/32"-3/16"	4.0-4.8	4"	102	.054	1.4	84	38	#13	.093		
	\$4 1/2	1/4"-9/32"	6.4-7.1	4"	102	.054	1.4	84	38	#11	.125		
	#4 1/2 RECT	1/4"-9/32"	6.4-7.1	4"	102	.052×.057	1.3×1.5	84	38	#13	.093		
	#5	9/32"-5/16"	7.1-7.9	5"	127	.054	1.4	84	38	#11	.125		
	#6	5/16"-3/8"	7.9-9.5	6"	152	.054	1.4	84	38	#9	.156		
	#7	3/8"-13/32"	9.5-10.3	6"	152	.054	1.4	84	38	#9	.156		
UNIBAR® SERIES	UX-1 SP	1/16"-1/8"	1.6-3.2	2"	51	.040	1.0	96	44	#25	.054-.065	Roller Lacer®.	Electric
	UX-1	1/8"-5/32"	3.2-4.0	2"	51	.040	1.0	96	44	#25	.054-.065	Microlacer™.	Hydraulic
	U1	1/8"-5/32"	3.2-4.0	3"	76	.054	1.4	84	38	#13	.093	#12 Lacer.With 12" .25" .38"	
	U2	5/32"-3/16"	4.0-4.8	3"	76	.054	1.4	84	38	#13	.093	(W/#1 Hook	
	U3	3/16"-7/32"	4.8-5.6	3 1/2"	89	.054	1.4	84	38	#13	.093	Retainer for	
	U4	7/32"-1/4"	5.6-6.4	5"	127	.054	1.4	84	38	#12	.109	UX-1 SP	
	U5	9/32"-5/16"	7.1-7.9	5"	127	.054	1.4	84	38	#11	.125	and UX-1)	